

Phacoemulsification apparatus includes a phacoemulsification handpiece (30) having a needle and an electrical system for ultrasonically vibrating said needle along with a power source (16) for providing electrical power to the handpiece electrical system. Irrigation fluid is provided to the handpiece needle and aspirating fluid is removed from the handpiece needle. A determination of a voltage current phase relationship of the provided electrical power is made and in response thereto a control system (22) varies a power level duty cycle provided to the handpiece electrical system from the power source and/or modify the aspiration flow rate.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

## PHASE CONTROLLED PHACOEMULSIFICATION

This application is a continuation-in-part of U.S. Patent Application Serial No. 09/206,452, filed on  
5 December 7, 1998, now abandoned, which is a continuation of U.S. Patent Application Serial No. 08/787,229, now U.S. 5,852,794.

The present invention is generally directed to a  
10 method and apparatus for controlling the flow of fluid from a source to a patient and removal of fluids from the patient through a phacoemulsification handpiece as well as controlling power provided to the phacoemulsification handpiece.

15 The flow of fluid to and from a patient through a fluid infusion or extraction system and power control to a phacoemulsification handpiece is many times critical to the procedure being performed.

20 A number of medically recognized techniques has been utilized for lens removal and among these, a popular technique is phacoemulsification, irrigation and aspiration. This method includes the making of a  
25 corneal incision, which is typically cauterized to reduce bleeding, and the insertion of a handheld surgical implement which includes a needle which is ultrasonically driven in order to emulsify the eye lens. Simultaneously with this emulsification, a fluid  
30 is inserted for irrigation of the emulsified lens and a vacuum provided for aspiration of the emulsified lens and inserted fluids.

Currently available phacoemulsification systems  
35 include a variable speed peristaltic pump, a vacuum

sensor, an adjustable source of ultrasonic power and a programmable microprocessor with operator-selected presets for controlling aspiration rate, vacuum and ultrasonic power levels.

5

Many surgical instruments and controls in use today linearly control the vacuum or linearly control the flow of aspiration fluid. This feature allows the surgeon to precisely "dispense" or control the "speed" at which he/she employs, either the vacuum or the flow, but not both. However, there often are times during surgery when the precise control when one of the variables (vacuum, aspiration rate, or ultrasonic power) is desired over the other. The experienced user, understanding the relationship between the vacuum and the flow, may manually adjust the preset variable appropriately at the console in order to obtain an acceptable performance. However, if this adjustment is overlooked, then the combination of both high vacuum and high flow can cause undesirable fluidic surges at the surgical site with possible damage inflicted on the patient.

It should be apparent that the control of handheld surgical instruments for use in phaco surgery is complex. Phacoemulsifier apparatus typically comprises a cabinet, including a power supply, peristaltic pump, electronic and associated hardware, and a connected, multi-function and handheld surgical implement, or handpiece, including a hollow slender-like needle tube as hereinabove described, in order to perform the phacoemulsification of the cataractous lens.

It should be appreciated that a surgeon utilizing the handheld implement to perform the functions hereinabove described requires easy and accessible control of these functions, as well as the ability to

selectively shift or switch between at least some of the functions (for example, irrigation and irrigation plus aspiration) as may arise during phacoemulsification surgery.

5

In view of the difficulty with adjusting cabinet-mounted controls, while operating an associated handheld medical implement, control systems have been developed such as described in U.S. Patent No. 10 4,983,901. This patent is to be incorporated entirely into the present application, including all specification and drawings for the purpose of providing a background to the complex controls required in phacoemulsification surgery and for describing 15 apparatus which may be utilized or modified for use with the method of the present invention.

To further illustrate the complexity of the control system, reference is also made to U.S. Patent 20 No. 5,268,624. This patent application is to be incorporated in the present application by this specific reference thereto, including all specifications and drawings for the purpose of further describing the state-of-the-art in the field of this 25 invention.

It should thus be apparent, in view of the complex nature of the control system of fluids and ultrasonic power in the case of phacoemulsification procedures, 30 that it is desirable for a surgeon to have a system which is programmable to serve both the needs of the surgical procedure and particular techniques of the surgeon, which may differ depending on the experience and ability of the surgeon.

35

The present invention more specifically relates to the control of fluid flow and power control to a

phacoemulsification handpiece based on the determination of the phase angle between voltage applied to a handpiece piezoelectric transducer and the current drawn by the piezoelectric transducer.

5

Phacoemulsification systems typically include a handpiece having an ultrasonically vibrated hollow needle and an electronic control therefor.

10 As is well known in the art, the phacoemulsification handpiece is interconnected with a control console by an electric cable for powering and controlling the piezoelectric transducer and tubing for providing irrigation fluid to the handpiece and  
15 withdrawing aspiration fluid from an eye through the handpiece.

The hollow needle of the handpiece is typically driven or excited along its longitudinal axis by the  
20 piezoelectric effect in crystals created by an AC voltage applied thereto. The motion of the driven crystal is amplified by a mechanically resonant system within the handpiece, such that the motion of the needle connected thereto is directly dependent upon the  
25 frequency at which the crystal is driven, with a maximum motion occurring at a resonant frequency.

The resonant frequency is dependent, in part upon the mass of the needle interconnected therewith, which  
30 is vibrated by the crystal.

For pure capacitive circuits, there is a 90 degree phase angle between a sine wave representing the voltage applied to the handpiece and the resultant  
35 current into the handpiece. This is expressed by the

angle  $\phi$  equaling -90 degrees. For a purely inductive circuit, the phase angle  $\phi$  equals + 90 degrees and, of course, for purely resistive circuits  $\phi =$  zero.

5 A typical range of frequency used for phacoemulsification handpiece is between about 30 kHz to about 50 kHz. A frequency window exists for each phacoemulsification handpiece that can be characterized by the handpiece impedance and phase.

10 This frequency window is bounded by an upper frequency and a lower cutoff frequency. The center of this window is typically defined as the point where the handpiece electrical phase reaches a maximum value.

15 At frequencies outside of this window, the electrical phase of the handpiece is equal to -90 degrees.

20 Handpiece power transfer efficiency is given by the formula  $(V \cdot I)(\cos \phi)$ . This means that the most efficient handpiece operating point occurs when the phase is closest to 0 degrees.

In order to maintain optimum handpiece power transfer efficiency, it is important to control the frequency to achieve a phase value as close to zero degrees as possible.

25 This goal is complicated by the fact that the phase angle of the ultrasonic handpiece is also dependent on the loading of the transducer which occurs through the mechanically resonant system which includes the needle.

30 That is, contact with the needle with tissue and fluids within the eye create a load on the piezoelectric crystals with concomitant change in the operating phase angle.

35 Consequently, it is important to determine and measure the phase angles at all times during operation of the handpiece in order to adjust the driving circuitry to achieve an optimum phase angle in order

to effect constant energy transfer into the tissue by the phaco handpiece, regardless of loading effects.

Thus, it is important to provide automatic tuning of the handpiece during its use in phacoemulsification tissue and withdrawing same from an eye. This auto tuning is accomplished by monitoring the handpiece electrical signals and adjusting the frequency to maintain consistency with selected parameters.

In any event, control circuitry for phacoemulsification handpiece can include circuitry for measuring the phase between the voltage and the current, typically identified as a phase detector. However, problems arise in the measurement of the phase shift without dependence on the operating frequency of the phacoemulsification handpiece. That is, because, as hereinabove noted, the phase shift is dependent on the operating frequency of the handpiece and air and time delay in the measurement thereof requires complex calibration circuitry in order to compensate to provide for responsive tuning of the handpiece.

Phase detection is the process of applying two electrical periodic signals of similar frequency into an electrical circuit that generates a voltage proportional to the time (phase) difference between the two signals.

This voltage generated by the phase detector is then usually time averaged either by an electronic circuit or sampled by an A/D converter and then averaged digitally.

The averaged signal can be read by a conventional voltage meter or used by a microprocessor as data for processing. The averaging also helps to reject electrical noise.

As was described earlier, the output of a phase detector is proportional to the difference in time (of occurrence) of two signals. By definition, this means



that while the electrical output of a conventional phase detector is a function of the signal phase, it is also directly proportional to the frequency of use. This means that the frequency of use must be known and compensated for when reading the phase detector output in order to derive quantified phase values. While, as hereinabove noted, a calibration circuit can account for the variation of the frequency, such a circuit is usually very complex and may require the use of a microcontroller. In addition, neither of these approaches account for the drift in performance over time which is typical of phacoemulsification handpieces.

This problem was recognized in U.S. Patent No. 5,431,664, which provided a solution by using the admittance of the transducers as the tuning parameter rather than the phase-angle. The necessary circuitry is, of course, complicated and accordingly there is still a continuing need for a method for determining real time electrical phase for a piezoelectric phacoemulsification handpiece which is consistent over the entire handpiece range of operation which does not require further calibration circuitry for the controller.

#### SUMMARY OF THE INVENTION

In accordance with the present invention, phacoemulsification apparatus in accordance with the present invention generally includes a phacoemulsification handpiece having a needle and an electrical means for ultrasonically vibrating the needle. The power source provides a means for supplying electrical power to the handpiece of electrical means and a means for providing irrigation to the handpiece needle and aspirating fluid from the

handpiece needle is also incorporated in the present invention.

5 A means for determining the voltage current phase relationship of the provided electrical power is provided and full means is provided for responding to the determination of phase for varying a power level provided to the handpiece electrical means from the power source means.

10

In one embodiment of the present invention, the control means is responsive to the determined voltage current phase relationship for varying a pulse duty cycle of the power supply to the handpiece.

15

In yet another embodiment of the present invention, the control means is responsive to the means for determining the phase relationship for varying an irrigation fluid rate provided to the handpiece.

20

In yet another embodiment of the present invention, the control means in response to the means for determining the phase relationship varies in aspiration fluid rate from the handpiece.

25

Importantly, the means for determining the voltage current phase relationship generally includes the means for obtaining an AC voltage signal corresponding to the operating AC voltage of a piezoelectric handpiece and  
30 means for obtaining an AC current signal corresponding to the operating AC current of the piezoelectric handpiece.

Means are provided for determining the onset of a  
35 current cycle from the AC current signal and means are also provided for producing a voltage ( $V_i$ ) corresponding

to a time necessary for the AC current to reach a maximum value after onset of the current cycle.

5        Additionally, means are provided for producing a voltage ( $V_v$ ) corresponding to a time necessary for the AC voltage to reach a maximum value after onset of the current cycle.

10        An A/D converter provides a means for comparing ( $V_v$ ) and ( $V_i$ ) to determine the phase relationship between the voltage and current of the piezoelectric phacoemulsification handpiece and generating a phase signal ( $S_p$ ) corresponding thereto, the phase signal being frequency independent.

15

      A method in accordance with the present invention for operating a phacoemulsification system which includes a phacoemulsification handpiece, and an ultrasonic power source, a vacuum source, a source of  
20    irrigating fluid, and a control unit having a vacuum sensor for controlling the aspiration of the irrigating fluid from the handpiece. The method includes the steps of placing the handpiece in an operative relationship with an eye for phacoemulsification  
25    procedure and supplying irrigation fluid from the irrigation fluid source to and through the handpiece and into the eye.

      Ultrasonic power is provided from the ultrasonic  
30    power source to the handpiece for performing the phacoemulsification procedure.

      A vacuum is applied from the vacuum source to the handpiece to aspirate the irrigating fluid from the eye  
35    through the handpiece at a selected rate.

A voltage current phase relationship of the power from the power source is determined and in response thereto, the ultrasonic power being provided to the handpiece is variably controlled.

5

In one embodiment of the present invention, the variable control of the power includes varying the pulse duty cycle of the supply power.

10 Another embodiment of the present invention, the invention includes variably controlling the response to the determined phase relationship, the irrigation fluid flow being supplied to the handpiece.

15 In yet another embodiment of the present invention, the method includes variably controlling in response to the determined phase relationship, the vacuum or aspiration being applied to the handpiece.

20 BRIEF DESCRIPTION OF THE DRAWINGS

The advantages and features of the present invention will be better understood by the following description when considered in conjunction with the  
25 accompanying drawings in which:

30

Figure 1 is a functional block diagram of a phacoemulsification system in accordance with the present invention;

Figure 2 is a functional block diagram of an alternative embodiment of a phacoemulsification system in accordance with the present invention which includes apparatus for providing irrigation fluid at more than  
35 one pressure to a handpiece;

Figure 3 is a flow chart illustrating the operation of the occluded-unoccluded mode of the phacoemulsification system with variable aspiration rates;

5

Figure 4 is a flow chart illustrating the operation of the occluded-unoccluded mode of the phacoemulsification system with variable ultrasonic power levels;

10

Figure 5 is a flow chart illustrating the operation of the variable duty cycle pulse function of the phacoemulsification system;

15

Figure 6 is a flow chart illustrating the operation of the occluded-unoccluded mode of the phacoemulsification system with variable irrigation rates;

20

Figure 7 is a plot of the 90 degree phase shift between the sine wave representation of the voltage applied to a piezoelectric phacoemulsification handpiece and the resultant current into the handpiece;

25

Figure 8 is a plot of the phase relationship and the impedance of a typical piezoelectric phacoemulsification handpiece;

30

Figure 9 is a block diagram of improved phase detector circuitry suitable for performing a method in accordance with the present invention;

35

Figure 10 is a plot of phase relationship as a function of frequency for various handpiece/needle loading;

Figure 11 is a function block diagram of a phase control phacoemulsification system utilizing phase angles to control handpiece/needle parameters with max phase mode operation; and

5

Figure 12 is a function block control diagram of a phase control phacoemulsification system utilizing phase angles to control handpiece/needle parameters with a load detect method.

10

#### DETAILED DESCRIPTION OF THE DRAWINGS

Turning now to the drawings, and particularly to Figure 1 thereof, there is shown, in functional block diagram form, a phacoemulsification system indicated generally by the reference numeral 10. The system has a control unit 12, indicated by the dashed lines in Figure 1 which includes a variable speed peristaltic pump 14, which provides a vacuum source, a source of pulsed ultrasonic power 16, and a microprocessor computer 18 that provides control outputs to pump speed controller 20 and ultrasonic power level controller 22. A vacuum sensor 24 provides an input to computer 18 representing the vacuum level on the output side of peristaltic pump 14. Suitable venting is provided by vent 26.

As hereinafter described in greater detail, a phase detector 28 provides an input to computer 18 representing a phase shift between a sine wave representation of the voltage applied to a handpiece/needle 30 and the resultant current into the handpiece 30. The block representation of the handle 30 includes a typical handpiece having a needle and electrical means, typically a piezoelectric crystal, for ultrasonically vibrating the needle.

The control unit 12 supplied ultrasonic power on line 32 to a phacoemulsification handpiece/needle 30. An irrigation fluid source 34 is fluidly coupled to handpiece/needle 30 through line 36. The irrigation fluid and ultrasonic power are applied by handpiece/needle 30 to a patient's eye which is indicated diagrammatically by block 38. Aspiration of the eye 38 is achieved by means of the control unit peristaltic pump 14 through lines 40 and 42.

10

The computer 18 responds to preset vacuum levels in output line 42 from peristaltic pump 14 by means of signals from the previously mentioned vacuum sensor 24. Operation of the control unit in response to the occluded-unoccluded condition of handpiece 30 is shown in the flow diagram of Figure 3.

As shown in Figure 3, if the handpiece aspiration line 40 is occluded, the vacuum level sensed by vacuum sensor 24 will increase. The computer 18 has operator-settable limits for aspiration rates, vacuum levels and ultrasonic power levels. As illustrated in Figure 3, when the vacuum level sensed by vacuum sensor 24 reaches a predetermined level as a result of occlusion of the handpiece aspiration line 40, computer 18 instructs pump speed controller 20 to change the speed of the peristaltic pump 14 which, in turn, changes the aspiration rate. It will be appreciated that, depending upon the characteristics of the material occluding handpiece/needle 30, the speed of the peristaltic pump 14 can either be increased or decreased. When the occluding material is broken up, the vacuum sensor 24 registers a drop in vacuum level, causing computer 18 to change the speed of peristaltic pump 14 to an unoccluded operating speed.

In addition to changing the phacoemulsification parameter of aspiration rate by varying the speed of the peristaltic pump 14, the power level of the ultrasonic power source 16 can be varied as a function of the occluded or unoccluded condition of handpiece 30. Figure 4 illustrates in flow diagram form the control of the ultrasonic power source power level by means of computer 18 and power level controller 22. It will be appreciated that the flow diagram of Figure 4 corresponds to the flow diagram of Figure 3 but varies the phacoemulsification parameter of the ultrasonic power level.

With reference to Figure 5, there is shown a flow diagram depicting the control of the ultrasonic power source 16 to produce varying pulse duty cycles as a function of selected power levels. As shown in Figure 5, and by way of illustration only, a 33% pulse duty cycle is run until the power level exceeds a preset threshold; in this case, 33%. At that point, the pulse duty cycle is increased to 50% until the ultrasonic power level exceeds a 50% threshold, at which point the pulse duty cycle is increased to 66%. When the ultrasonic power level exceeds 66% threshold, the power source is run continuously, i.e., a 100% duty cycle. Although the percentages of 33, 50 and 66 have been illustrated in Figure 5, it should be understood that other percentage levels can be selected to define different duty cycle shift points.

30

Turning back to Figure 2, there is shown an alternative embodiment 50 of a phacoemulsification system, in accordance with the present invention, and which incorporates all of the elements of the system 10 shown in Figure 1, with identical reference characters identifying components, as shown in Figure 1.



In addition to the irrigation fluid source 34, a second irrigation fluid source 35 is provided with the sources 34, 35 being connected to the line 36 entering the handpiece/needle 30 through lines 34a, 35a, respectively, and to a valve 38. The valve 38 functions to alternatively connect line 34a and source 34 and line 35a and source 35 with the handpiece/needle 30 in response to a signal from the power level controller 22 through a line 52.

10

As shown, irrigation fluid sources 34, 35 are disposed at different heights above the handpiece/needle 30 providing a means for introducing irrigation fluid to the handpiece at a plurality of pressures, the head of the fluid in the container 35 being greater than the head of fluid in the container 34. A harness 42, including lines of different lengths 44, 46, when connected to the support 48, provides a means for disposing the containers 34, 35 at different heights over the handpiece/needle 30.

The use of containers for irrigation fluids at the various heights is representative of the means for providing irrigation fluids at different pressures, and alternatively, separate pumps may be provided with, for example, separate circulation loops (not shown) which also can provide irrigation fluid at discrete pressures to the handpiece/needle 30 upon a command from the power controller 22.

30

With reference to Figure 5, if the handpiece aspiration line 38 is occluded, the vacuum level sensed by the vacuum sensor 24 will increase. The computer 18 has operator-settable limits for controlling which of the irrigation fluid supplies 32, 33 will be connected to the handpiece 30. It should be appreciated that

while two irrigation fluid sources, or containers 32, 33 are shown, any number of containers may be utilized.

As shown in Figure 6, when the vacuum level by the vacuum sensor 24 reaches a predetermined level, as a result of occlusion of the aspiration handpiece line 38, the computer controls the valve 38 causing the valve to control fluid communication between each of the containers 34, 35 and the handpiece/needle 30.

10

It should be appreciated that, depending upon the characteristics of the material occluding the handpiece/needle 30, as hereinabove described and the needs and techniques of the physician, the pressure of irrigation fluid provided the handpiece may be increased or decreased. As occluded material 24, the vacuum sensor 24 registers a drop in the vacuum level causing the valve 38 to switch to a container 34, 35, providing pressure at an unoccluded level.

20

As noted hereinabove, it should be appreciated that more than one container may be utilized in the present invention, as an additional example, three containers (not shown) with the valve interconnecting to select irrigation fluid from any of the three containers, as hereinabove described in connection with the Figure 1A container system.

In addition to changing phacoemulsification handpiece/needle 30 parameter as a function of vacuum, the occluded or unoccluded state of the handpiece can be determined based on a change in load sensed by a handpiece/needle by way of a change in phase shift or shape of the phase curve.

35

The typical range of frequencies used for phacoemulsification handpiece 30 is between about 30

kHz and about 50 kHz. When the frequency applied to the handpiece is significantly higher, or lower than resonancy, it responds electrically as a capacitor. The representation of this dynamic state is shown in Figure 7 in which curve 60 (solid line) represents a sine wave corresponding to handpiece 30 current and curve 62 (broken line) represents a sine wave corresponding to handpiece 30 voltage.

The impedance of the typical phacoemulsification handpiece 30 varies with frequency, i.e., it is reactive. The dependence of typical handpiece 30 phase and impedance as a function of frequency is shown in Figure 8 in which curve 64 represents the phase difference between current and voltage of the handpieces function frequency and curve 66 shows the change in impedance of the handpiece as a function of frequency. The impedance exhibits a low at "Fr" and a high "Fa" for a typical range of frequencies.

Automatic tuning of the handpiece, as hereinabove briefly noted, is typically accomplished by monitoring the handpiece electrical signals and adjusting the frequency to maintain a consistency with selected parameters.

In order to compensate for a load occurring at the tip of the phacoemulsification handpiece, the drive voltage to the handpiece can be increased while the load is detected and then decreased when the load is removed. This phase detector is typically part of the controller in this type of system.

In such conventional phase detectors, the typical output is a voltage as proportional to the difference in alignment of the voltage and the current waveform, for example, -90 degrees as shown in Figure 7. As

shown in Figure 8, it is important to consider that during the use of the handpiece, the waveform is varying in phase and correspondingly the output waveform is also varying.

5

Heretofore, the standard technique for measuring electrical phase has been to read a voltage that is proportional to phase and also to frequency. This type of circuit can be calibrated for use with a single frequency as changing the frequency would cause the calibration data to be incorrect.

This can also be seen with single frequency systems. The corrected phase value will drift due to variation in the circuit parameters.

This can also be seen with single frequency systems. The corrected phase value will drift due to variation in the circuit parameters.

20

The other typical approach is to utilize a microprocessor to compare the value of the phase detector output with that of a frequency detector and compute the true phase. This approach is fairly complex and is subject to drift of the individual circuits as well as resolution limitations.

A block diagram 70 as shown in Figure 9 is representative of an improved phase detector suitable for performing the method in accordance with the present invention. Each of the function blocks shown comprises conventional state-of-the-art circuitry of typical design and components for producing the function represented by each block as hereinafter described.

The voltage input 72 and current 74 from a phacoemulsification handpiece 30 is converted to an appropriate signal using an attenuator 76 on the voltage signal to the phacoemulsification handpiece, and a current sense resistor 78 and fixed gain amplifier for the handpiece 30 current.

Thereafter, an AC voltage signal 80 and AC current signal 82 is passed to comparators 84, 86 which convert the analog representations of the phacoemulsification voltage and current to logic level clock signals.

The output from the comparator 84 is fed into a D flip flop integrated circuit 90 configured as a frequency divide by 2. The output 92 of the integrated circuit 90 is fed into an operational amplifier configured as an integrator 94. The output 96 of the integrator 94 is a sawtooth waveform of which the final amplitude is inversely proportional to the handpiece frequency. A timing generator 98 uses a clock synchronous with the voltage signal to generate A/D converter timing, as well as timing to reset the integrators at the end of each cycle.

This signal is fed into the voltage reference of an A/D converter via line 96.

The voltage leading edge to current trailing edge detector 100 uses a D flip flop integrated circuit in order to isolate the leading edge of the handpiece voltage signal. This signal is used as the initiation signal to start the timing process between the handpiece 30 voltage and handpiece 30 current.

The output 102 of the leading detector 100 is a pulse that is proportional to the time difference in occurrence of the leading edge of the handpiece 30

voltage waveform and the falling edge of the handpiece current waveform.

Another integrator circuit 104 is used for the  
5 handpiece phase signal 102 taken from the detector 100. The output 106 of the integrator circuit 104 is a sawtooth waveform in which the peak amplitude is proportional to the time difference in the onset of leading edge of the phacoemulsification voltage and the  
10 trailing edge of the onset of the handpiece current waveform. The output 106 of the integrator circuit 104 is fed into the analog input or an A/D (analog to digital converter) integrated circuit 110.

15 Therefore, the positive reference input 96 to the A/D converter 110 is a voltage that is inversely proportional to the frequency of operation. The phase voltage signal 96 is proportional to the phase difference between the leading edge of the voltage  
20 onset, and the trailing edge of the current onset, as well as inversely proportional to the frequency of operation. In this configuration, the two signals Frequency voltage reference 96 and phase voltage 46 track each other over the range of frequencies, so that  
25 the output of the A/D converter 110 produces the phase independent of the frequency of operation.

The advantage of utilizing this approach is that the system computer 18 (see Figures 1 and 2) is  
30 provided with a real time digital phase signal that 0 to 255 counts will consistently represent 0 to 359 degrees of phase.

The significant advantage is that no form of  
35 calibration is necessary since the measurements are consistent despite the frequencies utilized.

For example, using AMPs operation frequencies of 38 kHz and 47 kHz and integrator having a rise time of  $150 \times 10^3 \text{V}/2$  and an 8 bit A/D converter having 256 counts, a constant ratio is maintained and variation in frequency does not affect the results. This is shown in the following examples.

10

15

20

25

30

35

EXAMPLE 1 - 38KHz OPERATION:

Period of 1 clock cycle =  $1/F @ 38\text{KHz} = 26.32 \times 10^{-6}\text{S}$

Portion of one period for  $I = 90$  degrees =  $26.32 \times 10^{-6}\text{S}/4 = 6.59 \times 10^{-6}\text{S}$

Integrator output for one reference cycle  
 $= (150 \times 10^3 \text{ V/S}) \times (26.32 \times 10^{-6}\text{S}) = 3.95 \text{ Volts}$

Integrator output from 90 degree cycle duration  
 $= (150 \times 10^3 \text{ V/S}) \times (6.59 \times 10^{-6}\text{S}) = .988 \text{ Volts}$

Resulting Numerical count from A/D converter  
 $= 3.95 \text{ Volts} / 256 \text{ counts} = .0154 \text{ Volts per count}$

Actual Number of A/D counts for 90 degrees at 38 KHz

EXAMPLE 2 - 47 KHz OPERATION:

Period of 1 clock cycle =  $1/F @ 47\text{KHz} = 21.28 \times 10^{-6}\text{S}$

Portion of one period for  $I = 90$  degrees =  $21.28 \times 10^{-6}\text{S}/4 = 5.32 \times 10^{-6}\text{S}$

Integrator output for one reference cycle  
 $= (150 \times 10^3 \text{ V/S}) \times (21.28 \times 10^{-6}\text{S}) = 3.19 \text{ Volts}$

Integrator output from 90 degree cycle duration  
 $= (150 \times 10^3 \text{ V/S}) \times (5.32 \times 10^{-6}\text{S}) = .798 \text{ Volts}$

Resulting Numerical count from A/D converter  
 $= 3.19 \text{ Volts} / 256 \text{ counts} = .0124 \text{ Volts per count}$

Actual Number of A/D counts for 90 degrees at 47 KHz  
 $= .798 / .0124 = 64 \text{ counts}$



A plot of phase angle as a function of frequency is shown in Figure 10 for various handpiece 30 loading, a no load (max phase), light load, medium load and heavy load.

5

With reference to Figure 11, representing max phase mode operation, the actual phase is determined and compared to the max phase. If the actual phase is equal to, or greater than, the max phase, normal aspiration function is performed. If the actual phase is less than the max phase, the aspiration rate is changed, with the change being proportionate to the change in phase.

15

Figure 12 represents operation at less than max load in which load (see Figure 10) detection is incorporated into the operation, a method of the present invention.

20

As represented in Figure 11, representing max phase mode operation, if the handpiece aspiration line 40 is occluded, the phase sensed by phase detector sensor 28 will decrease (see Figure 10). The computer 18 has operator-settable limits for aspiration rates, vacuum levels and ultrasonic power levels. As illustrated in Figure 11, when the phase sensed by phase detector 28 reaches a predetermined level as a result of occlusion of the handpiece aspiration line 40, computer 18 instructs pump speed controller 20 to change the speed of the peristaltic pump 14 which, in turn, changes the aspiration rate.

30

It will be appreciated that, depending upon the characteristics of the material occluding handpiece/needle 30, the speed of the peristaltic pump 14 can either be increased or decreased. When the occluding material is broken up, the phase detector 28

35

registers an increase in phase angle, causing computer 18 to change the speed of peristaltic pump 14 to an unoccluded operating speed.

5        In addition to changing the phacoemulsification parameter of aspiration rate by varying the speed of the peristaltic pump 14, the power level and/or duty cycle of the ultrasonic power source 16 can be varied as a function of the occluded or unoccluded condition  
10 of handpiece 30.

Although there has been hereinabove described a method and apparatus for controlling a phacoemulsification handpiece utilizing the voltage  
15 current phase relationship of the piezoelectric phacoemulsification handpiece in accordance with the present invention, for the purpose of illustrating the manner in which the invention may be used to advantage, it should be appreciated that the invention is not  
20 limited thereto. Accordingly, any and all modifications, variations, or equivalent arrangements which may occur to those skilled in the art, should be considered to be within the scope of the present invention as defined in the appended claims.

25

30

## WHAT IS CLAIMED IS:

1. Phacoemulsification apparatus comprising:
  - a phacoemulsification handpiece having a needle and electrical means for ultrasonically vibrating said needle;
  - power source means for providing electrical power to the handpiece electrical means;
  - means for providing irrigation fluid to the handpiece needle and aspirating fluid from the handpiece needle;
  - means for determining a voltage current phase relationship of the provided electrical power; and
  - control means for varying a power level provided to the handpiece electrical means from said power source means in response to the determined voltage current phase relationship of the provided electrical power.
2. The phacoemulsification apparatus according to claim 1 wherein said control means in response to the determined voltage current phase relationship for varying a pulse duty cycle of the power provided to the handpiece by said power source means.
3. Phacoemulsification apparatus comprising:
  - a phacoemulsification handpiece having a needle and electrical means for ultrasonically vibrating said needle;
  - power source means for providing electrical power to the handpiece electrical means;
  - means for providing irrigation fluid to the handpiece needle and aspirating fluid from the handpiece needle;
  - means for determining a voltage current phase relationship of the provided electrical power; and

control means for varying an irrigation fluid rate provided to the handpiece in response to the determined voltage current phase relationship of the provided electrical power.

5

4. Phacoemulsification apparatus comprising:

a phacoemulsification handpiece having a needle and electrical means for ultrasonically vibrating said needle;

10 power source means for providing electrical power to the handpiece electrical means;

means for providing irrigation fluid to the handpiece needle and aspirating fluid from the handpiece needle;

15 means for determining a voltage current phase relationship of the provided electrical power; and

control means for varying an aspiration fluid rate from the handpiece needle in response to the determined voltage current phase relationship of the  
20 provided electrical power.

5. The phacoemulsification apparatus according to any one of claims 1, 2, 3 and 4 wherein the means for determining a voltage current phase relationship  
25 comprises:

means for obtaining an AC voltage signal corresponding to the operating AC voltage of a piezoelectric handpiece;

30 means for obtaining an AC current signal corresponding to the operating AC current of the piezoelectric handpiece;

means for determining onset of a current cycle from said AC current signal;

35 means for producing a voltage ( $V_1$ ) corresponding to a time necessary for the AC current signal to reach a maximum value after onset of the current cycle;

means for producing a voltage ( $V_v$ ) corresponding to a time necessary for the AC voltage signal to reach a maximum value after onset of the current cycle; and

5           A/D converter means for comparing ( $V_v$ ) and ( $V_i$ ) to determine the phase relationship between the voltage and current of the piezoelectric phacoemulsification handpiece and generating a phase signal ( $S_p$ ) corresponding thereto, said phase signal  
10 being frequency independent.

6. A method for operating a phacoemulsification system, the system including a phacoemulsification handpiece, an ultrasonic power source, a vacuum source,  
15 a source of irrigating fluid, and a control unit having a vacuum sensor for controlling the aspiration of irrigating fluid from the handpiece, said operating method comprising the steps of:

(a) placing the handpiece in an operative  
20 relationship with an eye for a phacoemulsification procedure;

(b) supplying irrigation fluid from the irrigation fluid source to and through the handpiece and into said eye;

25 (c) providing ultrasonic power from the ultrasonic power source to the handpiece for performing the phacoemulsification procedure;

(d) applying vacuum from the vacuum source to the handpiece and thereby aspirating the irrigating fluid  
30 from the eye through the handpiece at a selected rate;

(e) determining a voltage current phase relationship of the power from the power source; and

(f) variably controlling, in response to the determined phase relationship, the ultrasonic power  
35 being provided to the handpiece.

7. The method according to claim 6 wherein the step of variably controlling the ultrasonic power comprises varying a pulse duty cycle of the power provided to the handpiece.

5

8. A method for operating a phacoemulsification system, the system including a phacoemulsification handpiece, an ultrasonic power source, a vacuum source, a source of irrigating fluid, and a control unit having  
10 a vacuum sensor for controlling ultrasonic power provided to the handpiece and the aspiration of irrigating fluid from the handpiece, said operating method comprising the steps of:

(a) placing the handpiece in an operative  
15 relationship with an eye for a phacoemulsification procedure;

(b) supplying irrigation fluid from the irrigation fluid source to and through the handpiece and into said eye;

20 (c) providing ultrasonic power from the ultrasonic power source to the handpiece for performing the phacoemulsification procedure;

(d) applying vacuum from the vacuum source to the handpiece and thereby aspirating the irrigating fluid  
25 from the eye through the handpiece at a selected rate;

(e) determining a voltage current phase relationship of the power from the power source; and

(f) variably controlling, in response to the determined phase relationship, the irrigation fluid  
30 flow being supplied to the handpiece.

9. A method for operating a phacoemulsification system, the system including a phacoemulsification handpiece, an ultrasonic power source, a vacuum source,  
35 a source of irrigating fluid, and a control unit having a vacuum sensor for controlling the aspiration of

irrigating fluid from the handpiece, said operating method comprising the steps of:

5 (a) placing the handpiece in an operative relationship with an eye for a phacoemulsification procedure;

(b) supplying irrigation fluid from the irrigation fluid source to and through the handpiece and into said eye;

10 (c) providing ultrasonic power from the ultrasonic power source to the handpiece for performing the phacoemulsification procedure;

(d) applying vacuum from the vacuum source to the handpiece and thereby aspirating the irrigating fluid from the eye through the handpiece at a selected rate;

15 (e) determining a voltage current phase relationship of the power from the power source; and

(f) variably controlling, in response to the determined phase relationship, the vacuum being applied to the handpiece.

20

10. The method according to any one of claims 6, 7, 8 or 9, wherein the step of determining a voltage current phase relationship comprises the steps of:

25 obtaining an AC voltage signal corresponding to the operating AC voltage of a piezoelectric handpiece;

obtaining an AC current signal corresponding to the operating AC current of the piezoelectric handpiece;

30 from said AC current signal, determining onset of a current cycle;

after onset of the current cycle, producing a voltage ( $V_i$ ) corresponding to a time necessary for the AC current signal to reach a maximum value;

35 after onset of the current cycle, producing a voltage ( $V_v$ ) corresponding to a time necessary for the AC voltage signal to reach a maximum value; and

using an A/D converter, to produce a digital output signal, ( $S_p$ );

by comparing ( $V_v$ ) to ( $V_i$ ), and determining the phase relationship between the voltage and current of the piezoelectric phacoemulsification handpiece, said phase signal ( $S_p$ ) being frequency independent.

11. The method according to claim 10 wherein the step of determining current cycle onset comprises determining when the AC current increases while crossing a zero current value.

12. The method according to claim 11 further comprising the step of producing a current onset signal and feeding same into the A/D converter.

13. The method according to claim 12 further including the step of providing an integration for producing the ( $V_v$ ) and ( $V_i$ ) voltage and feeding same into the A/D converter.

14. The method according to claim 13 further comprising the step of dividing the AC voltage signal by two, producing a divided voltage signal and feeding same along with the AC voltage signal into the integrator.

30

35



1/11




FIG. 1.







FIG. 2.


3/11

FIG. 3.

FIG. 4.

5/11

FIG. 5.

FIG. 6.




FIG. 7.




FIG. 8.






FIG. 9.



*FIG. 10.*

10/11

FIG. 11.




FIG. 12.

**A. CLASSIFICATION OF SUBJECT MATTER**  
 IPC 7 A61F9/007

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61F B06B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 852 794 A (STAGGS JAMES W) 22 December 1998 (1998-12-22) cited in the application	1, 5
Y	column 1, line 14 - line 19 column 3, line 52 - column 4, line 4; claim 1; figure 3	2-4
Y	US 5 700 240 A (BARWICK JR BILLIE JOHN ET AL) 23 December 1997 (1997-12-23) column 5, line 57 - column 6, line 29; figures 2-5	2-4
A	US 4 808 948 A (PATEL DIPAKKUMAR I ET AL) 28 February 1989 (1989-02-28) abstract; figure 3	1
	-/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

## \* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

2 August 2000

Date of mailing of the international search report

09/08/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
 NL - 2280 HV Rijswijk  
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
 Fax: (+31-70) 340-3018

Authorized officer

Mayer, E

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 520 633 A (COSTIN JOHN A) 28 May 1996 (1996-05-28) column 2, line 63 - line 68 <u>        </u>	1

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
US 5852794	A	22-12-1998	EP	0954386 A	10-11-1999
			WO	9831476 A	23-07-1998
US 5700240	A	23-12-1997	US	5591127 A	07-01-1997
			EP	0741554 A	13-11-1996
			JP	9508298 T	26-08-1997
			WO	9520374 A	03-08-1995
			AU	2735095 A	15-08-1995
US 4808948	A	28-02-1989	JP	1164484 A	28-06-1989
US 5520633	A	28-05-1996	US	5279547 A	18-01-1994
			US	5160317 A	03-11-1992
			AT	168259 T	15-08-1998
			AU	667801 B	18-04-1996
			AU	1229692 A	17-08-1992
			AU	697525 B	08-10-1998
			AU	4557096 A	23-05-1996
			AU	676980 B	27-03-1997
			AU	5196096 A	11-07-1996
			CA	2099780 A	04-07-1992
			DE	69226255 D	20-08-1998
			DE	69226255 T	24-12-1998
			EP	0565640 A	20-10-1993
			EP	0776643 A	04-06-1997
			ES	2121007 T	16-11-1998
			JP	2858949 B	17-02-1999
			JP	6506125 T	14-07-1994
			WO	9211814 A	23-07-1992
			MX	9200006 A	01-07-1992